
MIG200



Features:

- Rugged, robust, and industrial look with ergonomic design
- ***ClearVision*** Technology
- ***Intelligent synergic control***
- Welding engineer mode
- ***Smart Lift TIG***
- Consistent and efficient MIG spot welding performance
- Flexible remote control solutions
- Quick factory reset; auto sleep mode
- Compatible with MIG digital torch and spool gun
- LED inside wire feeder cabinet; handy accessory storage slot
- ***ABAP: Active Balancing Air Passage***
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



Specifications:

		MIG200 N2S32
Input power		AC230 V ±15%, 50/60 Hz
Open circuit voltage		60 V
MIG	Rated input current	46 A
	Rated input power capacity	8.85 kVA
	Output current range	30~200 A
	Rated duty cycle	30%
	Wire feed speed	2~15 m/min
	Wire spool size	D200
MMA	Rated input current	36 A
	Rated input power capacity	8.81 kVA
	Output current range	20~180 A
	Rated duty cycle	30%
TIG	Rated input current	32 A
	Rated input power capacity	7.53 kVA
	Output current range	5~200 A
	Rated duty cycle	30%
Efficiency		81.4%
Power factor		0.65
Idle state power		<50 W
Protection class		IP23S
Insulation class		H
Dimensions L×W×H		565×220×415 mm
Net weight		15 kg



Standard Accessories

- 3M MB-15 MIG torch
- 3M earth clamp
- 1 pc quick socket
- 2 pcs hose clamps

