

TIG200PACDC LCD

Features:

- Rugged, robust, and industrial look with ergonomic design
- Color LCD control panel
- HF stabilizing technology
- ***Dash-Arc***
- ***Smart Lift TIG***
- Job parameters saver
- Full-featured pulse TIG parameters
- Multiple AC waveforms
- Mixed waveform, mixed waveform frequency, mixed wave duty cycle
- Flexible remote control solutions
- Quick factory reset; auto sleep mode
- Water cooled option available
- ***ABAP: Active Balancing Air Passage***
- ***Smart gas*** for optimized shielding gas consumption
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



Specifications:

		TIG200P ACDC LCD E2S13
Input power		AC230 V ±15%, 50/60 Hz
Open circuit voltage		60 V
TIG	Rated input current	25 A
	Rated input power capacity	6.0 kVA
	Output current range	DC: 5~200 A AC: 20~200 A
	Rated duty cycle	25%
MMA	Rated input current	27 A
	Rated input power capacity	7.0 kVA
	Output current range	10~160 A
	Rated duty cycle	20%
Efficiency		80%
Power factor		0.75
Idle state power		<50 W
Protection class		IP23S
Insulation class		H
Dimensions L×W×H		490×165×341 mm
Net weight		11.7 kg





Standard Accessories

- 4M SGT26-S1 180A TIG torch
- 3M earth clamp
- 1 pc quick socket
- 2 pcs hose clamps